

Thales

wall light



Table of contents

1. Product overview	Page 2
2. Finishes and materials	Page 2
3. Light Source & dimming	Page 2
4. Functionality & accessories	Page 3
5. Photometric data and technical information	Page 3
6. Ordering codes	Page 4
7. Certifications & standards	Page 6
8. Maintenance & Cleaning	Page 6

Versions:



THA_4080 (Indoor version)
Page 4



THA_4080B (Bathroom version)
Page 5

Thales

wall light

1. Product overview

Metal wall light providing soft, diffused illumination through a satin-finished opal glass shade. The softly diffused light provides comfortable ambient illumination, while the front decorative disc adds a distinctive design detail and can be customized for signage. IP44 rated, it is ideal for bathroom and hospitality environments, combining functionality with refined aesthetics. Integrated dimmable LED.



2. Finishes and Materials



Shade: White Opal Glass

Body: 20 Metallic Gold
87 Bronze
96 Anthracite

3. Light Source & Dimming

Lamping (Indoor version)

LED 9W (2700K / Ang. 124° / >90 CRI / 350mA) 230V / Typ* 1430 lumens

*Integrated LED module (included).

Lamping (Bathroom version)

LED 6,2W (2700K / Ang. 124° / >90 CRI / 350mA) 230V / Typ* 725 lumens

*Integrated LED module (included).

Dimming options:

Standard: TRIAC

Optional: DALI, CASAMBI

Thales

wall light

4. Functionality & Accessories




Optional laser-cut signage.
Minimum order 10 units.

5. Photometric Data and Technical Information

Photometric data corresponds to the output of each individual lamp.
Access to photometric files in download area.


2D / 3D / BIM Files available.
Access to files in download area here

9W (indoor version)



H[m]	D[m]	Max lux	Med lux	Alpha=62.2°+62.2°	G=0.0 Máx no a G
1.00	3.80	58	10		
2.00	7.59	14	3		
3.00	11.39	6	1		
4.00	15.18	4	1		
5.00	18.98	2	0		

6,2W (bathroom version)



H[m]	D[m]	Max lux	Med lux	Alpha=62.2°+62.2°	G=0.0 Máx no a G
1.00	3.80	50	9		
2.00	7.59	12	2		
3.00	11.39	6	1		
4.00	15.18	3	1		
5.00	18.98	2	0		

Thales

wall light

6. Ordering Codes

Lamping (Indoor version)

LED 9W

(2700K / Ang. 124° / >90 CRI / 350mA)

230V / Typ* 1430 lumens

Dimming options

Standard: TRIAC

Optional: DALI, CASAMBI

Finishes:

20 Metallic Gold

87 Bronze

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
THA_4080 IP20 <p> \varnothing 116 mm \varnothing 4.5/8" \varnothing 110 mm \varnothing 4.3/8" \varnothing 220 mm \varnothing 8.5/8" 66 mm 2.5/8" \varnothing 220 mm \varnothing 8.5/8" </p>	Wall lamp. Surface mounted.	Indoor	Metallic Gold	THA_4080_20W
		Indoor	Bronze	THA_4080_87W
		Indoor	Anthracite	THA_4080_96W

Thales

wall light

6. Ordering Codes

Lamping (Bathroom version)

LED 6,2W

(2700K / Ang. 120° / >90 CRI / 350mA)

230V / Typ* 725 lumens

Dimming options

Standard: TRIAC

Optional: DALI, CASAMBI

Finishes:

20 Metallic Gold

87 Bronze

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
THA_4080B IP44 <p> $\varnothing 116 \text{ mm}$ $\varnothing 4.5/8''$ 66 mm $2.5/8''$ </p> <p> $\varnothing 110 \text{ mm}$ $\varnothing 4.3/8''$ </p> <p> $\varnothing 220 \text{ mm}$ $\varnothing 8.5/8''$ </p> <p> $\varnothing 220 \text{ mm}$ $\varnothing 8.5/8''$ </p>	Wall lamp. Surface mounted.	Bathroom	Metallic Gold	THA_4080B_20W
		Bathroom	Bronze	THA_4080B_87W
		Bathroom	Anthracite	THA_4080B_96W

7. Certifications & Standards

THA_4080     

THA_4080B     

Warranty: 2 years
100% made in Spain

8. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.